

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets

(11) Veröffentlichungsnummer:

(11) Publication number:

(11) Numéro de publication:

**EP 1 392 368 A0**

Internationale Anmeldung veröffentlicht durch die  
Weltorganisation für geistiges Eigentum unter der Nummer:

**WO 03/086487** (art. 158 des EPÜ).

International application published by the World  
Intellectual Property Organisation under number:

**WO 03/086487** (art. 158 of the EPC).

Demande internationale publiée par l'Organisation  
Mondiale de la Propriété sous le numéro:

**WO 03/086487** (art. 158 de la CBE).

**BEST AVAILABLE COPY**

**THIS PAGE BLANK (USPTO)**

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number  
**WO 03/086487 A1**

(51) International Patent Classification<sup>7</sup>: **A61L 9/03,**  
**A01M 1/20**

(21) International Application Number: **PCT/US03/10358**

(22) International Filing Date: **4 April 2003 (04.04.2003)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:  
60/371,162 10 April 2002 (10.04.2002) **US**  
10/267,417 9 October 2002 (09.10.2002) **US**

(71) Applicant: **S. C. JOHNSON & SON, INC.** [US/US];  
Robert A. Miller, 1525 Howe Street, Racine, WI 53403-  
2236 (US).

(72) Inventors: **STENICO, Filippo**; Via Anzoletti 4, I-38100  
Trento (IT). **MARCHETTI, Fabio**; Via Paho 18, I-38050  
Povo (IT). **DEFLORIAN, Stefano**; Via dei Castori

41/5, I-38040 Martignano (IT). **FRISANCO, Alessan-**  
**dro**; Via Nogarole 22, I-38049 Vigolo Vattaro (IT).  
**BALDESSARI, Stefano**; Via Roma 29, I-38052 Caldon-  
azzo (IT). **CAMPEDELLI, Paolo**; Via Divisione Aqui,  
34, I-38065 Mori (IT). **PEDROTTI, Andrea**; Via Piano  
Sarca 13, I-30070 Pietramurata (IT).


(74) Agents: **MILLER, Robert, A. et al.**; S. C. Johnson & Son,  
Inc., 1525 Howe Street, Racine, WI 53403 (US).

(81) Designated States (*national*): **AE, AG, AL, AM, AT, AU,**  
**AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,**  
**CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,**  
**GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,**  
**LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,**  
**MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,**  
**SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ,**  
**VC, VN, YU, ZA, ZM, ZW.**

(84) Designated States (*regional*): **ARIPO** patent (**GH, GM,**  
**KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW,**

[Continued on next page]

(54) Title: **ELECTRICAL EVAPORATOR INCLUDING FAN AND LOUVER STRUCTURE**



(57) Abstract: An evaporator, for use with a bottle containing a substance to be evaporated and a wick that has its lower portion disposed within the bottle and its upper portion protruding from the bottle, includes a housing in which the bottle is retained, a fan, disposed within the housing, for creating an airstream, and a louver structure, disposed downstream of the fan, for directing the airstream created by the fan upwardly and away from the upper portion of the wick. Preferably, the louver structure includes a plurality of louvers inclined at an angle between about 20 degrees to about 60 degrees relative to horizontal.

WO 03/086487 A1



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

*with international search report*

## **ELECTRICAL EVAPORATOR INCLUDING FAN AND LOUVER STRUCTURE**

### **RELATED APPLICATION**

**[0001]** This application claims the benefit of U.S. Provisional Patent Application No. 60/371,162, filed April 10, 2002.

### **BACKGROUND OF THE INVENTION**

#### **1. Field of the Invention**

**[0002]** The present invention relates generally to an electrical evaporator for use with liquid formulations containing a chemical active such as an insecticide, a fragrance, an odor eliminator, or the like, and, in particular, to an electrical evaporator including a fan and a louver structure that helps to achieve a beneficial distribution of the chemical active within a surrounding environment, such as a room.

-2-

## 2. Description of the Related Art

[0003] Plug-in electrical evaporators for dispersing chemical actives such as insecticides and fragrances are well known in the art. For the most part, however, these known evaporators fail to achieve an optimal distribution of the chemical active within their surrounding environment. Insecticides, for example, should be concentrated in areas where insects are most likely to come into contact with a person's skin. Fragrances, on the other hand, should be most concentrated at nose level. We have found that known plug-in evaporators generally undersaturate the "living areas" of a room where the chemical active is most likely to come in contact with a person's skin or nose, and oversaturate the non-living areas of a room, such as the floor, ceiling, and walls. This results in a waste of chemical active and a decrease in the overall effectiveness of the evaporator.

## SUMMARY OF THE INVENTION

[0004] The present invention provides an electrical evaporator that produces a beneficial distribution of the chemical active within a surrounding environment.

[0005] According to one aspect of the invention, an evaporator, for use with a bottle containing a substance to be evaporated and a wick that has its lower portion disposed within the bottle and its upper portion protruding from the bottle, includes (i) a

-3-

housing for retaining the bottle, (ii) a fan, disposed within the housing, for creating an airstream, and (iii) a louver structure, disposed downstream of the fan, for directing the airstream created by the fan upwardly and away from the upper portion of the wick.

[0006] In another aspect, the present invention relates to an evaporator including (i) a bottle containing a substance to be evaporated, (ii) a wick, having a lower portion disposed within the bottle and an upper portion protruding from the bottle, for drawing the substance to be evaporated from the bottle toward the upper portion of the wick, (iii) a housing in which the bottle is retained, (iv) means, within the housing, for creating an airstream, and (v) means for directing the airstream upwardly and away from the upper portion of the wick.

[0007] In still another aspect, the present invention relates to a plug-in evaporator for dispersing a chemical active into a surrounding environment. The evaporator includes (i) a bottle containing a liquid formulation including at least one chemical active, (ii) a wick, having a lower portion disposed within the bottle and an upper portion protruding from the bottle, for drawing the liquid formulation from the bottle toward the upper portion of the wick, (iii) a housing in which the bottle is detachably retained, (iv) an electrical heating device, disposed within the housing at a position proximate to the upper portion of the wick, for enhancing evaporation of the liquid formulation from the upper portion of the wick, (v) a fan, disposed within the

-4-

housing, for creating an airstream that entrains the evaporated liquid formulation, and (vi) an electrical plug, extending from the housing, for supplying power to the heating device and the fan and for supporting the evaporator in a wall outlet. The housing includes a plurality of louvers located downstream from the fan for directing the airstream created by the fan upwardly and away from the heating device and the upper portion of the wick. Preferably, the louvers are inclined at an angle between about 20 degrees to about 60 degrees relative to horizontal when the evaporator is in an upright position.

[0008] A better understanding of these and other features and advantages of the invention may be had by reference to the drawings and to the accompanying description, in which preferred embodiments of the invention are illustrated and described.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 is a perspective view of an evaporator according to a preferred embodiment of the present invention.

[0010] FIG. 2 is a rotated perspective view of the evaporator shown in FIG. 1.

[0011] FIG. 3 is an exploded assembly view of the evaporator shown in FIG. 1.



[0012] FIG. 4 is a front elevation view of the evaporator shown in FIG. 1, with the intensity setting on low.

[0013] FIG. 5 is a cross-sectional view taken along section line A-A in FIG. 4.

[0014] FIG. 6 is a cross-sectional view taken along section line B-B in FIG. 4.

[0015] FIG. 7 is a front elevation view of the evaporator shown in FIG. 1, with the intensity setting on high.

[0016] FIG. 8 is a cross-sectional view taken along section line C-C in FIG. 7.

[0017] FIG. 9 is a cross-sectional view taken along section line D-D in FIG. 7.

[0018] FIG. 10 is a cross-sectional view taken along section line E-E in FIG. 7.

[0019] FIG. 11 is a schematic diagram of a preferred electrical circuit for the evaporator shown in FIG. 1.

[0020] Throughout the figures, like or corresponding reference numerals have been used for like or corresponding parts.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0021] An evaporator 100 according to a preferred embodiment of the present invention is illustrated in FIGS. 1-11.

[0022] As shown in FIG. 1, the evaporator 100 comprises a multi-piece housing 110 in which a bottle 120 is detachably retained. The bottle 120 contains an evaporable substance (not shown), such as, for example, a liquid formulation including a chemical active such as an insecticide, fragrance, odor eliminator, or the like. The term "bottle" is used herein in its broadest possible sense, including any receptacle, container, pouch, etc., capable of holding a liquid formulation. A raised pattern 130 on one side of the bottle is engaged by an opening 140 in a front shell 150 of the evaporator housing 110, while a similar raised pattern 160 (shown in FIG. 6) on an opposite side of the bottle 120 is engaged by a recess 170 (shown in FIG. 3) in a middle shell 180, in order to secure the bottle 120 within the evaporator 100. The front shell 150 is sufficiently pliant so that pulling the bottle 120 in a downward direction causes the raised patterns 130, 160 to release from the opening 140 in the front shell 150 and the recess 170 in the middle shell 180, respectively, thereby enabling removal of the bottle 120 from the evaporator 100. Alternatively, the neck portion of the bottle may be designed to snap or screw into the evaporator housing. Suitable refill bottles are available in a wide

-7-

variety of liquid formulations from S.C. Johnson & Son, Inc., of Racine, Wisconsin, under the GLADE® PLUGINS® and RAID® brand names.

[0023] As shown in FIG. 3, the bottle 120 includes a wick 190 for drawing the liquid formulation out of the bottle 120 and toward an upper portion of the wick 190. A lower portion of the wick 190 is immersed in the liquid formulation, and the upper portion of the wick 190 protrudes above the neck of the bottle 120. Preferably, the wick 190 is positioned within the bottle 120 by a cap 200 which includes a sheath 210 that encases the upper portion of the wick 190, except for an open area near the tip of the wick 190. Alternatively, a cap without a sheath can be utilized. Preferably, the wick is about 7 mm in diameter and is constructed of ultra high molecular weight high density polyethylene.

[0024] In the preferred embodiment illustrated in FIGS. 1-10, the evaporator housing 110 comprises three shells — the front and middle shells 150, 180 noted above and a back shell 220 — which are fastened together by heat-staking or any other suitable fastening means, including, for example, rivets, press fit, snap fit, screws, ultrasonic welding, adhesives, or the like. The electrical components (discussed in more detail below) of the evaporator 100 are housed within the space enclosed by the middle and back shells 180, 220.

-8-

[0025] Referring to FIG. 2, the back shell 220 contains a circular opening in which a known electrical plug assembly 230 is seated. The plug 230 serves the dual purpose of supplying power to the electrical components of the evaporator 100 and also supporting the evaporator 100 in a wall outlet (not shown). Preferably, the plug assembly 230 is rotatable 360 degrees in order to support the evaporator 100 in an upright position in both horizontal and vertical wall outlets. Advantageously, the plug assembly 230 can be provided with an extra outlet which, as illustrated in FIG. 1, is located on the side of the evaporator 100 when the evaporator is plugged into a vertical wall outlet, and on the bottom of the evaporator 100 when the evaporator is plugged into a horizontal wall outlet (not shown).

[0026] As schematically illustrated in FIG. 3, the plug assembly 230 is electrically connected to a circuit board 240, which, in turn, is electrically connected to a heating device 250 and, preferably, also to a fan unit 260. The heating device 250 is disposed adjacent to a window 270 in the middle shell 180 which faces the tip of the wick 190 when the bottle 120 is inserted in the evaporator 100. Heating the wick 190 enhances the rate at which the liquid formulation evaporates into the surrounding environment, as described more fully below. Preferably, the heating device 250 is a 1.9 k $\Omega$ , 7 W metal oxide resistor potted in a ceramic block. The resistor preferably has PTC (positive temperature coefficient) characteristics, meaning that its resistance value increases slightly as the resistor heats up. A suitable resistor is available from Great Land Enterprise Co., Ltd., of Shenzhen, China, for example. Alternatively, the heating

-9-

device 250 can comprise one or more other types of resistor heaters, a wire-wound heater, a PTC heater, or the like.

[0027] The fan unit 260 is disposed within an upper portion of the housing 110. The back shell 220 includes air inlets 280 (shown in FIG. 2) for supplying air to the fan unit 260. As described more fully below, the fan unit 260 creates an airstream that entrains the evaporated liquid formulation and assists in the dispersion of the chemical active into the surrounding environment. Preferably, the flow rate of the fan unit 260 within the evaporator 100 is approximately 0.5 cubic feet per minute, and the fan speed is approximately 2800-3800 RPM. A suitable fan unit 260 is a 12 V, DC, brushless fan, such as available from Power Logic Tech. Inc., of Tapei-Hsien, Taiwan. Alternatively, other DC or AC fans could be utilized, with appropriate adjustments to the circuit board 240, which is described more fully below.

[0028] FIG. 11 is a schematic diagram of a preferred circuit board 240 for the evaporator 100. Preferably, the circuit board 240 is constructed of a flame-rated material. The circuit board 240 includes pins 600, 610 that connect to bus bars (not shown) of the plug assembly 230. The voltage applied across the pins 600, 610 is 120 V, at a frequency of 60 Hz. The heating device 250 is connected to the circuit board 240 by a pair of rivets 620, 630. Connected in parallel are (i) a 15 V, 1.3 W Zener diode 640, (ii) a 22  $\mu$ F, 50 V aluminum electrolytic capacitor 650, rated for a temperature of 105 °C, and (iii) the fan unit 260. The circuit board 240 also includes a

-10-

1N 4007 diode 660. The power consumption across the entire circuit is about 3.5 W to about 4.0 W. Those skilled in the art will appreciate that numerous alternative circuit configurations are also possible.

[0029] Immediately downstream of the fan unit 260 is a louver structure 290, shown in FIG. 3, comprising at least one louver and, more preferably, a plurality of louvers 300. Preferably, the louver structure 290 is an integral part of the middle shell 150, but it can also be provided separately from the middle shell 150. As illustrated in FIGS. 3 and 10, the louvers 300 are angled upwardly and away from the heating device 250 and the upper portion of the wick 190, preferably at an angle between about 20 degrees to about 60 degrees relative to horizontal when the evaporator 100 is in an upright position.

[0030] The optimum louver angle varies depending on such factors as the fan speed and the air exchange rate within the room in which the evaporator 100 is located. In rooms with relatively low air exchange rates (e.g., between about 0.6 to about 1.2 exchanges per hour), a louver angle of about 40 degrees to about 45 degrees relative to horizontal is preferred. In rooms with higher air exchange rates, a louver angle of about 25 degrees to about 30 degrees relative to horizontal is preferred.

[0031] The middle shell 180 is shaped so as to direct the airstream created by the fan unit 260 through the louvers 300. Notably, the middle shell 180 does not permit stray currents of air to recirculate within the housing 110, where those currents could have an

-11-

undesirable cooling effect on the heating device 250. A pair of openings 225 (shown in FIG. 2) in the side of the evaporator 100 helps to achieve proper air circulation through the evaporator.

[0032] The front shell 150 includes a plurality of vents 310 through which the airstream exits the evaporator 100 after passing through the louvers 300. As the airstream exits the evaporator 100 through the vents 310, it entrains the evaporated liquid formulation, which rises from the wick 190 through an opening 320 in the front shell 150 below the vents 310.

[0033] Tests have demonstrated that an evaporator constructed in accordance with the present invention disperses higher concentrations of the chemical active within the central "living area" of a room, as opposed to the walls, floor, or ceiling.

[0034] Those skilled in the art will appreciate that the benefits of the fan unit 260 and louver structure 290 described above can be achieved even in the absence of a heating device 250.

[0035] Optionally, the evaporator 100 also includes an adjustment mechanism 330 that positions the upper portion of the wick 190 with respect to the heating device 250. Preferably, the adjustment mechanism 330 includes a hollow cylindrical portion 340 that surrounds and engages part of the upper portion of the wick 190, preferably at a

-12-

location where the wick 190 is encased by the sheath 210. The adjustment mechanism 330 also includes a dial portion 350, accessible from outside the evaporator housing 110, for rotating the cylindrical portion 340 about an axis of rotation. The dial portion 350 preferably is formed integrally with the cylindrical portion 340, although it need not be.

[0036] Preferably, as shown in FIG. 5, a plurality of tapered lugs 360 is provided on the inner surface of the cylindrical portion 340. The lugs 360 are widest at their uppermost point, where they come in contact with the wick 190, and narrowest near the bottom of the cylindrical portion 340. At their uppermost point, the lugs 360 define a circular opening 370 that is just large enough for the wick 190 to fit through. The center of this opening 370 is offset relative to the axis of rotation of the cylindrical portion 340.

[0037] Rotating the dial portion 350 of the adjustment mechanism 330 causes the wick 190 to move toward or away from the heating device 250 in a lateral direction, i.e., in a direction substantially perpendicular to the longitudinal axis of the wick 190. In the minimum intensity setting illustrated in FIGS. 4-6, the axis of the wick 190 is positioned about 6.3 mm from the heating device 250. In this position, the wick is heated to a temperature of about 71-78 °C. Rotating the dial portion 350 approximately 75 degrees to the right brings the wick axis to a position that is about 4.4 mm from the heating device 250. At this maximum setting, which is illustrated in FIGS. 7-9, the wick is heated to a temperature of about 85-90 °C, thereby resulting in a higher



-13-

evaporation rate. The evaporator 100 also can be set to an intensity level anywhere in between the minimum and maximum settings. The lateral distance traveled by the wick 190 in moving from the minimum intensity setting to the maximum intensity setting is preferably between about 1 mm and about 3.5 mm. In the particular preferred embodiment described above, the lateral distance traveled by the wick 190 is about 2 mm.

[0038] Weight loss tests have demonstrated that the evaporation rate is almost 300 percent higher at the maximum setting than at the minimum setting.

[0039] The embodiments discussed above are representative of preferred embodiments of the present invention and are provided for illustrative purposes only. They are not intended to limit the scope of the invention. Although specific structures, dimensions, components, etc., have been shown and described, such are not limiting. Modifications and variations are contemplated within the scope of the present invention, which is intended to be limited only by the scope of the accompanying claims.

#### INDUSTRIAL APPLICABILITY

[0040] The present invention provides an electrical evaporator for use with liquid formulations containing a chemical active such as an insecticide, fragrance, odor eliminator, or the like. The evaporator includes a fan and a louver structure for

-14-

directing an airstream created by the fan upwardly and away from a wick, which is saturated with the liquid formulation. As the liquid formulation evaporates from the wick, it is entrained in the airstream and dispersed into the surrounding environment. The fan and louver structure help to achieve a beneficial distribution of the chemical active within the surrounding environment, so that the chemical active is more highly concentrated in areas where it is most likely to be effective, and less concentrated in other areas. This results in more efficient use of the chemical active.

-15-

## WE CLAIM:

1. An evaporator, for use with a bottle containing a substance to be evaporated and a wick that has its lower portion disposed within the bottle and its upper portion protruding from the bottle, the evaporator comprising:
  - a housing for retaining the bottle;
  - a fan, disposed within the housing, for creating an airstream; and
  - a louver structure, disposed downstream of the fan, for directing the airstream created by the fan upwardly and away from the upper portion of the wick.
2. The evaporator of claim 1, wherein the louver structure includes at least one louver which is inclined at an angle between about 20 degrees to about 60 degrees relative to horizontal when the evaporator is in an upright position.
3. The evaporator of claim 1, wherein the louver structure includes at least one louver which is inclined at an angle of about 25 degrees to about 30 degrees relative to horizontal when the evaporator is in an upright position.
4. The evaporator of claim 1, wherein the louver structure includes at least one louver which is inclined at an angle of about 40 degrees to about 45 degrees relative to horizontal when the evaporator is in an upright position.

-16-

5. The evaporator of claim 1, wherein the bottle is detachably retained within the housing.
6. The evaporator of claim 1, wherein the substance to be evaporated is one of an insecticide, a fragrance, or an odor eliminator.
7. The evaporator of claim 1, further comprising an electrical plug for supplying power to the fan and for supporting the evaporator in a wall outlet.
8. The evaporator of claim 7, wherein the electrical plug is rotatable in order to support the evaporator in an upright position in both horizontal and vertical wall outlets.
9. The evaporator of claim 1, further comprising an electrical heating device, disposed within the housing at a position proximate to the upper portion of the wick, for enhancing evaporation of the substance to be evaporated.
10. An evaporator, comprising:
  - a bottle containing a substance to be evaporated;
  - a wick, having a lower portion disposed within the bottle and an upper portion protruding from the bottle, for drawing the substance to be evaporated from the bottle toward the upper portion of the wick;

-17-

a housing in which the bottle is retained;

means, within the housing, for creating an airstream; and

means for directing the airstream upwardly and away from the upper portion of the wick.

11. The evaporator of claim 10, wherein the directing means comprises a plurality of louvers which are inclined at an angle between about 20 degrees to about 60 degrees relative to horizontal when the evaporator is in an upright position.

12. The evaporator of claim 10, wherein the directing means comprises a plurality of louvers which are inclined at an angle of about 25 degrees to about 30 degrees relative to horizontal when the evaporator is in an upright position.

13. The evaporator of claim 10, wherein the directing means comprises a plurality of louvers which are inclined at an angle of about 40 degrees to about 45 degrees relative to horizontal when the evaporator is in an upright position.

14. The evaporator of claim 10, wherein the bottle is detachably retained within the housing.

15. The evaporator of claim 10, wherein the substance to be evaporated is one of an insecticide, a fragrance, or an odor eliminator.

-18-

16. The evaporator of claim 10, wherein the means for creating an airstream comprises a fan.

17. The evaporator of claim 16, further comprising an electrical plug for supplying power to the fan and for supporting the evaporator in a wall outlet.

18. The evaporator of claim 17, wherein the electrical plug is rotatable in order to support the evaporator in an upright position in both horizontal and vertical wall outlets.

19. The evaporator of claim 10, further comprising an electrical heating device, disposed within the housing at a position proximate to the upper portion of the wick, for enhancing evaporation of the substance to be evaporated.

20. A plug-in evaporator for dispersing a chemical active into a surrounding environment, the evaporator comprising:

- a bottle containing a liquid formulation including at least one chemical active;
- a wick, having a lower portion disposed within the bottle and an upper portion protruding from the bottle, for drawing the liquid formulation from the bottle toward the upper portion of the wick;

- a housing in which the bottle is detachably retained;

-19-

an electrical heating device, disposed within the housing at a position proximate to the upper portion of the wick, for enhancing evaporation of the liquid formulation from the upper portion of the wick;

a fan, disposed within the housing, for creating an airstream that entrains the evaporated liquid formulation; and

an electrical plug, extending from the housing, for supplying power to the heating device and the fan and for supporting the evaporator in a wall outlet,

wherein the housing includes a plurality of louvers located downstream from the fan for directing the airstream created by the fan upwardly and away from the heating device and the upper portion of the wick, the louvers being inclined at an angle between about 20 degrees to about 60 degrees relative to horizontal when the evaporator is in an upright position.

21. The evaporator of claim 20, wherein the louvers are inclined at an angle of about 25 degrees to about 30 degrees relative to horizontal when the evaporator is in an upright position.


22. The evaporator of claim 20, wherein the louvers are inclined at an angle of about 40 degrees to about 45 degrees relative to horizontal when the evaporator is in an upright position.


-20-

23. The evaporator of claim 20, wherein the liquid formulation is one of an insecticide, a fragrance, or an odor eliminator.

24. The evaporator of claim 20, wherein the electrical plug is rotatable in order to support the evaporator in an upright position in both horizontal and vertical wall outlets.



**FIG. 1**

**FIG. 2**








FIG. 3




**FIG. 4**


**FIG. 5**


**FIG. 6**

**FIG. 7**

**FIG. 8**



**FIG. 9**



**FIG. 10**




FIG. 11

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 03/10358

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 A61L9/03 A01M1/20

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 A01M A61L B60H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)  
EPO-Internal, WPI Data, PAJ, FSTA, INSPEC, COMPENDEX

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 00 69479 A (JOHNSON & SON INC S C) 23 November 2000 (2000-11-23) page 1, line 22 -page 2, line 24 page 4, line 20 -page 5, line 28 figure 7 claims 1-22	1-24
X	DE 40 33 926 A (WOHLAND PETER ; ZIELONKA LOTHAR (DE)) 2 October 1991 (1991-10-02) column 1, line 55 -column 2, line 45 figures 1,2	1-24
X	US 3 633 881 A (YURDIN ALFRED) 11 January 1972 (1972-01-11) column 1, line 19 - line 50 column 3, line 16 - line 44 figures 2,5 claims 1-12	1-24
-/-		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*g\* document member of the same patent family

Date of the actual completion of the international search

3 July 2003

Date of mailing of the international search report

11/07/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Menidjel, R

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US. 03/10358

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 396 557 A (DELUCA RAYMOND F) 2 August 1983 (1983-08-02) column 2, line 37 - column 3, line 56 figure 1	1-24
A	US 5 647 053 A (SMITH KEVIN W ET AL) 8 July 1997 (1997-07-08) column 1, line 24 - line 32 column 2, line 13 - line 23 figure 1 claim 1	1-24


# INTERNATIONAL SEARCH REPORT


Information on patent family members

International Application No


PCT/US 03/10358

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0069479	A	23-11-2000	US 6361752 B1	26-03-2002
			AT 230616 T	15-01-2003
			AU 758871 B2	03-04-2003
			AU 5035000 A	05-12-2000
			BR 0010727 A	19-02-2002
			CA 2374014 A1	23-11-2000
			DE 60001166 D1	13-02-2003
			EP 1178842 A1	13-02-2002
			ES 2185596 T3	01-05-2003
			JP 2002543929 T	24-12-2002
			WO 0069479 A1	23-11-2000
DE 4033926	A	02-10-1991	DE 9003654 U1	28-06-1990
			DE 4033926 A1	02-10-1991
US 3633881	A	11-01-1972	NONE	
US 4396557	A	02-08-1983	AU 530675 B2	28-07-1983
			AU 5181579 A	24-04-1980
			CA 1140041 A1	25-01-1983
			CA 1145244 A2	26-04-1983
			CA 1158186 A2	06-12-1983
			DE 2966532 D1	16-02-1984
			DK 258880 A	17-06-1980
			EP 0019626 A1	10-12-1980
			EP 0098916 A2	25-01-1984
			IT 1123889 B	30-04-1986
			JP 55500799 T	16-10-1980
			NO 793342 A	21-04-1980
			NZ 191657 A	30-09-1983
			WO 8000792 A1	01-05-1980
US 5647053	A	08-07-1997	AU 702408 B2	18-02-1999
			AU 7246696 A	30-04-1997
			BR 9610894 A	28-09-1999
			CA 2234646 C	19-11-2002
			CN 1199346 A	18-11-1998
			EP 0854736 A1	29-07-1998
			JP 2000501167 T	02-02-2000
			NZ 319851 A	30-08-1999
			WO 9713539 A1	17-04-1997
			ZA 9608556 A	17-06-1997


**FIG. 1**

**FIG. 2**







319





**FIG. 4**

**FIG. 5**





**FIG. 6**

**FIG. 7**



**FIG. 8**

**FIG. 9**



**FIG. 10**






FIG. 11

**THIS PAGE BLANK (USPTO)**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**